

Translucent white vinyl featuring a permanent adhesive. This material has been specifically designed for digital printing on large-format inkjets and is suitable for printing with eco solvent and solvent inks as well as UV-cured inks.

## IP 2516

This material is a white matt calendered translucent vinyl, suitable for use on a wide variety of clean, dry surfaces. IP 2516 has been formulated to promote brilliant and colourful images with a medium to long-term, exterior durability. This translucent vinyl can be used in most interior applications and many exterior decorative and illuminated display applications (e.g. light boxes). Laminate: N/A

Specifications	
DESCRIPTION	Polymeric, translucent vinyl
COLOUR	White matt
FACE FILM THICKNESS	80 $\mu$
WEIGHT	N/A
ADHESIVE	Solvent acrylic, permanent
ADHESIVE STRENGTH	18N / 25mm (Finat TM 1/24h)
RELEASE PAPER	PE-coated silicone paper, 140g / m <sup>2</sup>
TEMPERATURE RANGE	-40°C to +80°C
DURABILITY (UNPRINTED)	Up to 7 years
FLAME RETARDANCY	Adhered to steel, self-extinguishing
SHELF LIFE	2 years, 20°C / 50% humidity
RECOMMENDATION	For optimum quality, please ensure that the media feed adjustment has been completed for this material

© January 2007 Spandex Group. Technical specifications subject to change without prior notice. All trademarks mentioned are property of their respective owners. Output may vary depending on the type of print data/file, application, media, environmental conditions, print speed, or other variables.